

SODIUM BICARBONATE

Coarse Granular Grade 5

Product Specification Sheet

Granulation: Typical Values

(Cumulative % Retained)

<u>Sieve Size</u>	<u>Micron</u>	<u>Minimum</u>	<u>Maximum</u>
+ 60 Mesh	250	0	35
+ 70 Mesh	212	0	50
+ 100 Mesh	150	25	100
+ 170 Mesh	90	70	100

Typical Bulk Density, lbs./ft³ (g/l): 75 (1200)

Applicable Standards: Meets AWWA.

Applicable Certifications: Kosher and Kosher Passover

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither Solvay Chemicals, Inc. nor any of its affiliates makes any warranty, express or implied, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use, the manner of use and whether any patents are infringed. This information gives typical properties only and is not to be used for specification purposes.

Trademarks: Trademarks and/or other Solvay Chemicals, Inc. products referenced herein are either trademarks or registered trademarks of Solvay Chemicals, Inc. or its affiliates, unless otherwise indicated.

Before using, read the Material Safety Data Sheet (MSDS) for the chemical.



Solvay
Chemicals



Interox, Fluorides & Minerals